

Mood Based Music Classification

Susheel Sharma¹, Rakesh Singh Jadon²

¹Department of Computer Applications MITS,
Gwalior, M.P. 474005, India

²Department of Computer Applications MITS,
Gwalior, M.P. 474005, India

Abstract

Due to enhancement in technology in the recent years lots of music is available as handy media for various devices. Thus there is an urgent need of analyzing music for storage, indexing and retrieval. In this paper we aimed at classifying music on the basis of their moods. We have identified three moods for this purpose: happy, angry and sad. These cognitive styles have few things in common. Identifying and extracting these features is a challenging problem. On the basis of our observations and literature review we have identified the eight features namely energy, entropy, zero-crossing rate, spectral rolloff, spectral centroid, spectral flux, RMS of signal and MFCC. After extracting features we have used neural network based training for classification. We have used Matlab 7.0.1 neural net tool for this purpose. We have populated a database of 150 songs consisting of 50 songs of each category. In this population 90 songs are used for training set and 60 for testing. The experimental results demonstrate the effectiveness of our classification system. We have obtained an overall accuracy of nearly 75%. The complete system is developed in MATLAB 7.0.1 including the GUI of the system.

Keywords: Audio samples, neural networks, mood classification, learning, matlab.

1.0 INTRODUCTION

With the growing market of portable digital audio players, the number of digital music files inside personal computers has increased. It can be difficult to choose and classify which songs to listen to when you want to listen to specific mood of music, such as happy music, sad music and angry music. Not only must the consumer classify their music, but online distributors must classify thousands of songs in their databases for their consumers to browse through.

In music psychology and music education, emotions based components of music has been recognized as the most strongly component associated with music expressivity. Music information behavior studies have also identified music mood emotion as an important criterion used by people in music seeking indexing and storage. However, evaluation of music mood is difficult to classify as it is highly subjective. Although there seems to be a very strong connectivity between the music (the audio) and the mood of a person. There are many entities which explicitly change our mood while we are listening music. Rhythm, tempo, instruments and musical scales are some such entities. There is one very important entity in the form of lyrics which directly affects our minds. Identifying audible words from lyrics and classifying the mood accordingly is a difficult problem as it includes complex issues of Digital Signal Processing. We have explored rather a simple approach of understanding the mood on the basis of audio patterns. This problem resembles to classical problem of

pattern recognition. We have made an effort to extract these patterns from the audio as audio features.

There can be other music moods also like- bored, sleepy, passionate, tensed, calm, relaxed etc. which seems to be difficult to classify. Therefore we have limited our problem on three prominent moods namely happy, angry and sad.

How can music be easily classified without human interaction? It would be extremely tedious to go through all of the songs in a large database one by one to classify them. A neural network could be trained to determine the difference between three different moods of music: happy music, sad music and angry music.

For this work, we have taken 90 sample songs for training, 30 songs for each mood and analyzed the 10 lakhs samples from the middle part of the each song to classify the music. Frequency content of the audio files can be extracted using the Fast Fourier Transformation in Matlab. The songs were recorded at a sampling rate of 22.05 KHz, so the largest recoverable frequency is 11.025 KHz.

We have collected approximately ten lakhs of music samples. From these samples of a song we have extracted 8 important features. These features are then actually used to classify the song. We have done classification using the feed-forward neural network. Firstly we train the Neural Network using training data set obtained from the Internet [30]. This trained neural network is then used for classification.

2.0 Literature Review

Music mood classification is the process of assigning moods such as happy, angry and sad. Different pieces of music in the same mood are thought to share the same “basic musical language”.

The most common of the categorical approaches to emotion modeling is that of Paul Ekman’s[1] basic emotions, which encompasses the emotions of anger, fear, sadness, happiness, and disgust. A categorical approach is one that consists of several distinct classes that form the basis for all other possible emotional variations. Categorical approaches are most applicable to goal-oriented situations.

A dimensional approach classifies emotions along several axes, such as valence (pleasure), arousal (activity), and potency (dominance). Such approaches include James Russell’s two-dimensional bipolar space (valence-arousal) [2], Robert Thayer’s energy-stress model [4,5] where contentment is defined as low energy/low stress, depression as low energy/high stress, exuberance as high energy/low stress, and anxious/frantic as high energy high stress, and Albert Mehrabian’s three-dimensional PAD representation (pleasure-arousal-dominance) [6].

One of the publications on emotion detection in music is credited to Feng, Zhuang, and Pan. They employ Computational Media Aesthetics to detect mood for music information retrieval tasks [7]. The two dimensions of tempo and articulation are extracted from the audio signal and are mapped to one of four emotional categories; happiness, sadness, anger, and fear. This categorization is based on both Thayer’s model [51] and Juslin’s theory [8], where the two elements of slow or fast tempo and staccato or legato articulation adequately convey emotional information from the performer to the audience. The time

domain energy of the audio signal issued to determine articulation while tempo is determined using Dixon's beat detection algorithm [9].

Single modal and multi modal mood classification has been done by various researchers. Kate Hevner's Adjective Circle[10] consists of 66 adjectives that are divided into 8 circles(which consists of moods). Chetan et al [11] chose emotional states based on Hevner's circle for their motion-based music visualization using photos. The eight classes in the order of the numbers are called: sublime,sad, touching, easy, light, happy, exciting and grand.

Farnsworth modified Hevner's concept and arranged the moods in ten groups [12].

Rigg et al [13,14] experiment includes four categories of emotion; lamentation, joy, longing, and love. Categories are assigned several musical features, for example 'joy' is described as having iambic rhythm (staccato notes), fast tempo, high register, major mode, simple harmony,and loud dynamics (forte) .

Watson et al[58] study is different from those of Hevner and Rigg because he uses fifteen adjective groups in conjunction with the musical attributes pitch (low-high), volume (soft-loud), tempo (slow-fast), sound (pretty-ugly), dynamics (constant-varying), and rhythm (regular irregular). Watson's research reveals many important relationships between these musical attributes and the perceived emotion of the musical excerpt. As such, Watson's contribution has provided music emotion researchers with a large body of relevant data that they can now use to gauge the results of their experiments

Automatic mood classification for music is a comparatively common technique. The used musical attributes are typically divided into two groups, timbre-based attributes

and rhythmic or tempo-based attributes. The tempo-based attributes can be represented by e.g. an Average Silence Ratio or a Beats per Minute value.

Lu [16] uses amongst others Rhythm Strength, Average Correlation Peak, Average Tempo and Average Onset Frequency to represent rhythmic attributes. Frequency spectrum based features like Mel- Frequency Cepstral Coefficients(MFCC), Spectral Centroid, Spectral Flux or Spectral Rolloff are also used.

Wu and Jeng [17] use a complex mixture of various features: Rhythmic Content, Pitch Content, Power Spectrum Centroid, Inter-channel Cross Correlation, Tonality, Spectral Contrast and Daubechies Wavelet Coefficient Histograms. For the classification step in the music domain Support Vector Machines (SVM) [18] and Gaussian Mixture Models (GMM) [19] are typically applied. Liu et al. [20] utilize a nearest-mean classifier. The comparison of classification results of different algorithms is difficult because every publication uses an individual test set or ground-truth. E.g. the algorithm of Wu and Jeng[17] reaches an average classification rate of 74,35% for 8 different moods with the additional difficulty that the results of the system and the ground- truth contain mood histograms which are compared by quadratic-cross-similarity. Jadon et al[21,22] have extracted time domain, pitch, frequency domain, sub band energy, and MFCC based audio features .

Another integral emotion detection project is Liand Ogihara's content-based music similarity search [23]. Their original work in emotion detection in music [27] utilized Farnsworth's ten adjective groups [13]. Li and Ogihara's system extracts relevant audio descriptors using MARSYAS [24] and then classifies them using Support Vector Machines (SVM). The 2004 research utilized

Hevner's eight adjective groups to address the problem of music similarity search and emotion detection in music. Daubechies Wavelet Coefficient Histograms are combined with timbral features, again extracted with MARSYAS, and SVMs were trained on these features to classify their music database implementing Tellegen, Watson, and Clark's three-layer dimensional model of emotion [25], Yang and Lee developed a system to disambiguate music emotion using software agents[26]. This platform makes use of acoustical audio features and lyrics, as well as cultural metadata to classify music by mood. The emotional model focuses on negative affect, and includes the axes of high/low positive affect and high/low negative affect. Tempo is estimated through the autocorrelation of energy extracted from different frequency bands. Timbral features such as spectral centroid, spectral rolloff, spectral flux, and kurtosis are also used to measure emotional intensity.

.Another implementation of Thayer's dimensional model of emotion is Tolos, Tato, and Kemp's mood-based navigation system for large collections of musical data [27]. In this system a user can select the mood of a song from a two-dimensional mood plane and automatically extract the mood from the song. Tolos, Tato, and Kemp use Thayer's model of mood, which comprises the axes of quality (x-axis) and activation (y-axis). This results in four mood classes, aggressive, happy, calm, and melancholic.

Building on the work of Li and Ogihara, Wiczorkowska, Synak, Lewis, and Ras conducted research to automatically recognize emotions in music through the parameterization of audio data [28]. They implemented a k-NN classification algorithm to determine the mood of a song. Timbre and chords are used as the primary features for parameterization. Their system implements single labeling

of classes by a single subject with the idea of expanding their research to multiple labeling and multi-subject assessments in the future. This labeling resulted in six classes: happy and fanciful; graceful and dreamy; pathetic and passionate; dramatic, agitated, and frustrated; sacred and spooky; and dark and bluesy.

Lastly, an emerging source of information relating to emotion detection in music is the Music Information Retrieval Evaluation eXchange's (MIREX)[29] annual competition, which will for the first time include an audio music mood classification category⁵. This MIR community has recognized the importance of mood as a relevant and salient category for music classification. They believe that this contest will help to solidify the area of mood classification and provide valuable ground truth data. At the moment, two approaches to the music mood taxonomy are being considered. The first is based on music perception, such as Thayer's two-dimensional model. It has been found that fewer categories result in more accurate classifications. The second model comes from music information practices, such as All Music Guide and MoodLogic, which use mood labels to classify their music databases. Social tagging of music, such as Last.FM, is also being considered as a valuable resource for music information retrieval and music classification.

3.1 Characterizing the mood using audio elements

The overall schematic diagram in order to classify the mood of the songs is shown in figure 1. The input to the system is a song in wav form, while the output is a mood of the defined types. The following figure reflects the methodology to implement the system.




Figure 1

We have taken the song as input and using Matlab’s **wavread** function we sampled the audio WAV file and convert it into text format. These functions sample the audio signal at 44.1 KHz and stored in the text files. Sampling is a process of converting continuous time domain signal into discrete signal. It can be done in matlab using “**wavread**” function. wavread supports multichannel data, with up to 32 bits per sample, and supports reading 24- and 32-bit .wav files. We then extracted the audio based features: entropy of the signal, energy of the signal, zero crossing rate, spectral rolloff, spectral centroid, spectral flux, RMS of the signal, and MFCC form the sampled file. A feed forward neural network is created in this step. The network is formed by selecting the best set of network attributes. Two hidden layers are taken each layer contains 10 neurons and default activation functions are used for each layer. The network is trained with the features matrix of 90 songs of three different moods. Number of epochs is selected to 1000, training goal is set to 0.1, learning rate is set to 0.05, training time to 32, mem_reduc is set to 2 etc. After successful training the network is then tested to the known moods songs. Basically network is tested to draw out the

efficiency rate. Testing ensures implementation of the system.

The network efficiency can be improved by applying certain techniques that are based on the concept of probabilistic reasoning. Baye’s Theorem is one such concept. If one found satisfying results after applying Baye’s reasoning it can then be implemented to increase the efficiency rate but again remember it is purely based on probabilistic reasoning, thus there are issues in adopting this concept.

Bayes' Theorem is a theorem of probability theory originally stated by the Reverend Thomas Bayes. It can be seen as a way of understanding how the probability that a theory is true is affected by a new piece of evidence. It has been used in a wide variety of contexts, ranging from marine biology to the development of "Bayesian" spam blockers for email systems. In the philosophy of science, it has been used to try to clarify the relationship between theory and evidence. Many insights in the philosophy of science involving confirmation, falsification, the relation between science and pseudoscience, and other topics can be made more precise, and sometimes extended or corrected, by using Bayes' Theorem. These pages will introduce the theorem and its use in the philosophy of science.

Begin by having a look at the theorem, displayed below. Then we'll look at the notation and terminology involved.

$$P(A/B)= (P(A) * P(B/A)) / P(B)$$

Where,

P(A) and P(B) are probability of two events A and B.

P(A/B) signifies probability of event A if event B is true.

P(B/A) signifies probability of event B if event A is true.

3.1 Features Extraction for Music Classification

Feature extraction requires an in-depth understanding of the signal processing theories. In this chapter we will be discussing the theoretical aspects of these features and feature extraction process.

1) Entropy: Entropy is a property that can be used to determine the energy not available for work. It is also a measure of the tendency of a process. It is a measure of disorder of a system.

Entropy refers to the relative degree of randomness. The higher the entropy, the more frequently are signaling errors. Entropy is directly proportional to the maximum attainable data speed in bps. Entropy is directly proportional to noise and bandwidth. It is inversely proportional to compatibility.

Entropy also refers to disorder deliberately added to data in certain encryption process.

2) Energy: Signal energy refers to strength of signal amplitude. In signal processing, the energy E_s of a continuous-time signal $x(t)$ is defined as

$$E_s = \langle x(t), x(t) \rangle = \int_{-\infty}^{\infty} |x(t)|^2 dt$$

Energy in this context is not, strictly speaking, the same as the conventional notion of energy in physics and the other sciences. The two concepts are, however, closely related, and it is possible to convert from one to the other:

$$E = \frac{E_s}{Z} = \frac{1}{Z} \int_{-\infty}^{\infty} |x(t)|^2 dt$$

where Z represents the magnitude, in appropriate units of measure, of the load driven by the signal.

For example, if $x(t)$ represents the potential (in volts) of an electrical signal propagating across a transmission line, then Z would represent the characteristic impedance (in ohms) of the transmission line. The units of measure for the signal energy E_s would appear as volt²-seconds, which is *not* dimensionally correct for energy in the sense of the physical sciences. After dividing E_s by Z , however, the dimensions of E would become volt²-seconds per ohm, which is equivalent to joules, the SI unit for energy as defined in the physical sciences.

3) Zero Crossing Rate: It refers to number of times the signal crosses zero line. The **zero-crossing rate** is the rate of sign-changes along a signal, i.e., the rate at which the signal changes from positive to negative or back. This feature has been used heavily in both speech recognition

and music information retrieval, being a key feature to classify percussive sounds [2].

ZCR is defined formally as

$$zcr = \frac{1}{T-1} \sum_{t=1}^{T-1} \mathbb{I}\{s_t s_{t-1} < 0\}$$

where s is a signal of length T and the indicator function $\mathbb{I}\{A\}$ is 1 if its argument A is true and 0 otherwise.

In some cases only the "positive-going" or "negative-going" crossings are counted, rather than all the crossings - since, logically, between a pair of adjacent positive zero-crossings there must be one and only one negative zero-crossing.

For monophonic tonal signals, the zero-crossing rate can be used as a primitive pitch detection algorithm

4) Spectral Rolloff: Flatness of sound. The decrease in energy with increase in frequency, ideally described in the sound source as 12 dB per octave. Spectral rolloff is defined as the frequency where 85% of the energy in the spectrum is below this point. It is often used as an indicator of the skew of the frequencies present in a window.

5) Spectral Flux: It determines changes of spectral energy (variation of harmonics). A feature extractor that extracts the Spectral Flux from a window of samples and the proceeding window. This is a good measure of the amount of spectral change of a signal.

Spectral flux is calculated by first calculating the difference between the current value of each magnitude spectrum bin in the current window from the corresponding value of the magnitude spectrum of the previous window. Each of these differences is then squared, and the result is the sum of the squares.

6) Spectral Centroid: Spectral Centroid is the balancing point of sub-band energy distribution. It determines the frequency area around which most of the signal energy concentrates and is thus closely related to the time domain ZCR feature.

It is also frequently used as approximation for a perceptual brightness measure. A feature extractor that extracts the Spectral Centroid. This is a measure of the "centre of mass" of the power spectrum.

This is calculated by calculating the mean bin of the power spectrum. The result returned is a number from 0 to 1 that represents at what fraction of the total number of bins this central frequency is.

7) Root Mean Square: It refers to the mathematical implementation of root of mean of square of the signal value (discrete sampled value). A feature extractor that extracts the Root Mean Square (RMS) from a set of samples. This is a good measure of the power of a signal.

RMS is calculated by summing the squares of each sample, dividing this by the number of samples in the window, and finding the square root of the result.

8) MFCC (Mel Frequency Cepstral Coefficient): Mel-frequency cepstral coefficients (MFCCs) are coefficients that collectively make up an MFC. The **mel-frequency cepstrum (MFC)** is a representation of the short-term power spectrum of a sound, based on

a linear cosine transform of a log power spectrum on a nonlinear mel scale of frequency.

They are derived from a type of cepstral representation of the audio clip (a nonlinear "spectrum-of-a-spectrum"). The difference between the cepstrum and the mel-frequency cepstrum is that in the MFC, the frequency bands are equally spaced on the mel scale, which approximates the human auditory system's response more closely than the linearly-spaced frequency bands used in the normal cepstrum. This frequency warping can allow for better representation of sound, for example, in audio compression.

MFCCs are commonly derived as follows:

1. Take the Fourier transform of (a windowed excerpt of) a signal.
2. Map the powers of the spectrum obtained above onto the mel scale, using triangular overlapping windows.
3. Take the logs of the powers at each of the mel frequencies.
4. Take the discrete cosine transform of the list of mel log powers, as if it were a signal.
5. The MFCCs are the amplitudes of the resulting spectrum.

3.2 Learning and Classification using Neural Network

Learning using neural network requires input feature matrix and output target matrix. The input feature matrix is created from discrete samples values of the input songs for training by calculating different audio features values.

We have taken the song as input and using Matlab's **wavread** function we sampled the audio WAV file and convert it into text format. These functions sample the audio signal at 44.1 Khz and stored in the text files. We then extract the audio based features entropy of the signal, energy of the signal, zero crossing rate, spectral rolloff, spectral centroid, spectral flux, RMS of the signal, and MFCC form the sampled file.

We then supply the extracted audio features and their expected outcomes as inputs to create the network. The classifier is implemented using MATLAB's Neural Networking toolbox. The classifier is a feed forward neural network with back propagation learning algorithm. Once the classifier is trained we simulate the classifier and get the mood of the song.

Process of creating Feedforward Neural Network:

Collect data: We have taken 90 songs (30 for each category : happy, sad and angry). We have extracted 10 lakhs discrete samples from the middle part of song's signal to reduce the length of each song. Then we have calculated the values of seven features described above using matlab script. We have prepared feature input matrix of each song which will be given as input to a feed forward neural network. Network consists of 2 hidden Layers with 10 neurons

each and 1 output layer with 3 neurons. The transfer function of 2 hidden layers is “tansig” and “purelin” respectively and the transfer function of the output layer is “logsig”.

Configure the network :

In this process we can change the attribute values of network to make the network learn in an efficient way.

Matlab code of configuring a network-

```
net.trainParam.epochs=1000;  
net.trainParam.goal=.1;  
net.trainParam.lr=0.05;  
net.trainParam.time=32;  
net.trainParam.mem_reduc=2;
```

where,

epochs signifies number of iterations of network.

goal signifies tolerance range under which output can vary.

lr is learning rate, which is one of the parameters which governs how fast a neural network learns and how effective the training is.

Time signifies time taken by neural network to learn.

Mem_reduc is an attribute which signifies reducing the memory to increase efficiency.

Initialize the weights and biases :

The *configure* command configures the network object and also initializes the weights and biases of the network; therefore the network is ready for training. There are times when you might want to reinitialize the weights, or to perform a custom initialization. Initializing Weights (init) explains the details of the initialization process. You can also skip the configuration step and go directly to training the network. The *train* command will automatically configure the network and initialize the weights.

Weights are saved in network attributes “**net.iw**”.

Train the network:

Once the number of layers, and number of units in each layer, has been selected, the network's weights and thresholds must be set so as to minimize the prediction error made by the network. This is the role of the *training algorithms*.

Train function is used to train the network.

Matlab code to train the network:-

```
net=train(net,p,t);  
save 'network.mat' 'net';
```

Where

“**net**” is the network variable

“**p**” is input feature matrix

“**t**” is target matrix

Save function is used to save the network “net” in the file named “network.mat”

Test the network:

Testing is done to check whether the network is producing the desired output or not. We tested the network with 45 songs (15 for each category).

Use the network: If the testing is successful and the efficiency of results is around 60-70% then we can use the network to test the new songs of unknown mood by simulating the saved trained network.

4.0 Implementations, Results and Discussions

We have implemented this system on windows platform in MATLAB 7.0.1. Both GUI and the classifier is implemented using MATLAB. Initially we have collected the database of various Hollywood songs in WAV format. We have taken songs from all three moods. Out of all songs we have reserved 90 songs for training purpose, 30 songs from each of the three mood i.e. happy, angry and sad. Songs are then sampled and samples are then cut to fixed lengths i.e. 10 lakhs samples from middle of each song. The 8 selected audio features are then extracted from each song and features values of all 90 songs are stored in a feature matrix. This feature matrix is used as input feature matrix with 8 rows containing features values and 90 columns for 90 songs, for training the neural network. Each column of this matrix represents features of one song. An output target matrix is constructed according to the input matrix representing the known mood of the 90 songs. The output target matrix contains 3 rows representing mood and 90 columns for 90 songs.

Neural Network can be created using “newff” function in Matlab. NEWFF Creates a feed-forward back propagation network. Since there are 8 input features, initially we started with 6 hidden neurons. We ran the training and testing sets through the network 10 times. But there was always the requirement to have right set of attribute values and the result of the simulation of the network is not good as expected. Therefore we then have chosen 2 hidden layers each layer containing 10 neurons. The no. of iterations (epoch) is most important. We kept the no. of epochs to 1000. Though maximum amount of learning is done by 2000 epochs but it is by 1000 that the learning curve becomes nearly horizontal. The performance function

value (goal) is kept to .01 during the training process. Values around .002-.003 are the minimum performance function values that we reach during the training and the networks trained up to these values produced satisfactory results .So we keep the value to .01 because by that value the network would really be trained enough. Learning rate is kept to .05. The no. of epochs after which the status of the level of training done is displayed (show) is kept to 50. Other parameters are kept to default value. This time network is trained 10 times to obtain the network that can be efficiently adopted after adjusting some network parameters. Then after training with 10 hidden neurons and fixed set of network attribute values we have computed the results. In order to increase the efficiency rate we have applied probabilistic reasoning through “Bayes theorem”.

4.1 Performance Evaluation

Performance evaluation can be done by testing the network with different songs with known mood and check their efficiency rate.

With the 8 important features selected, the approach was to determine how well the multilayer feed forward neural network would classify the songs. First, we determined how many hidden neurons should be in the hidden layer of the network.

We have extracted a clip from a song (between 30-50 secs) and started the training. When we have tested these results we didn’t get the desired efficiency so we have decided to have a different approach. After testing the new results obtained we have noticed that this time the testing gives better efficiency. Table-1

shows the results of this new testing scheme, a comparison is shown between tested results through the system and the original known mood the songs:

Statistics 10Lakhs		
song name	original mood	result_10L
Activate	Angry	Angry
Addicted	Sad	Angry
Ajks	Angry	Sad
Alldcold	Sad	Sad
Amyrica	Angry	Sad
Backst	Sad	Angry
beastie boys	Angry	Happy
Beforewebegu n	Sad	Happy
Blameit	Sad	Sad
Bottomsup	Angry	Angry
Breakstuff	Angry	Happy
Breathme	Sad	Sad
Brick	Sad	Sad
Burndown	Angry	no category
burnground	Angry	Angry
Camarada	Happy	Happy
Careless	Happy	Happy
chickenwire	Sad	Sad
claymoreparty	Angry	Sad

Statistics 10Lakhs		
song name	original mood	result_10L
comacinema	Sad	Angry
Crawling	Angry	Angry
dontgiveup	Angry	Happy
drowningpool	Angry	Angry
Dwayim	Angry	Angry
Emptiness	Sad	Sad
Escape	Sad	Angry
Everysec	Sad	Happy
Flowers	Sad	Sad
gloomysunday	Sad	no category
Mtoj	Happy	Happy
Myheart	Happy	Happy
Papi	Happy	no category
Rightnow	Sad	Sad
theme of son	Angry	Angry
Tiktok	Happy	Happy
ucantseeme	Happy	Happy

Table -1

We can see here in this testing we got 18 out 36 songs are correctly matched. These 10 lakhs samples were from the start of the song that does not ensure correctness because samples may have continuous

zeros in the starting duration which would not be efficient.

Therefore we have decided to have another approach and extracted samples from middle part of the song. We have taken 10 lakhs fixed length samples from the middle part of every song and then repeated the process. Since there are 8 input features, initially we started with 6 hidden neurons. We ran the training and testing sets through the network 10 times. But there was always the requirement to have right set of attribute values. This time network is trained 10 times to obtain the network that can be efficiently adopted after adjusting some network parameters. This time we then have chosen 2 hidden layers each layer containing 10 neurons. The network goal, learning rate and training time is adjusted such that to have the best network that could be selected after modifying the parameters values and testing some songs hand in hand. Then after training with 10 hidden neurons and fixed set of network attribute values we have computed the results. In order to increase the efficiency rate we have applied probabilistic reasoning through “Baye’s theorem”.

Method of increasing efficiency:

$P(A)$ is maximum component of any of the mood.

$P(B)$ refers to the case when a song does not belong to any of the category and the output matrix is $[0;0;0]$ (zero matrix).

$P(B/A)$ refers to the probability of output matrix is zero matrix when the maximum component refers to original mood of the song.

Thus, the probability of maximum component refers to the original mood when the output matrix is zero matrix.

In our case,

$$P(A)=24/42;$$

$$P(B)=6/42;$$

$$P(B/A)=3/24;$$

$$P(A/B)=((24/42)*(3/24))/(6/42);$$

$$=1/2 = 50\%$$

Baye’s Theorem gives satisfying results, thus we’ve decided to implement Baye’s Theorem to increase our efficiency rate. Statistics obtained after applying Baye’s Theorem are is shown in Table-2

Test Statistics Table		
Song name	original mood	tested result
Activate	Angry	Angry
Addicted	sad	Angry
Ajks	angry	Angry
all d cold	sad	angry
Amyrica	angry	Angry
Backst	sad	Happy
beastie boys	angry	Angry
before we begun	sad	Sad

Test Statistics Table		
Song name	original mood	tested result
blame it	sad	Happy
bottoms up	angry	no category
break stuff	angry	Happy
breathe me	sad	Sad
Brick	sad	Sad
burn down	angry	Angry
burn ground	angry	Angry
Camarada	happy	Sad
Careless	happy	Angry
chicken wire	sad	Sad
clay more party	angry	Sad
coma cinema	sad	Happy
Crawling	angry	Angry
dont give up	angry	Angry
drowning pool	angry	Happy
Emptiness	Sad	Sad
Escape	Sad	Angry
every second	Sad	Sad
Flowers	Sad	Sad
gloomy Sunday	Sad	Sad
heal the world	Happy	Sad

Test Statistics Table		
Song name	original mood	tested result
Mtoj	Happy	Sad
my heart	Happy	Happy
null sleep	Happy	Happy
Papi	Happy	Angry
right now	Sad	Angry
stuck in infinity	Sad	Sad
the guest	Sad	Sad
the way We am	Angry	no category
theme of son	Angry	Angry
Tiktok	Happy	happy and angry
United	Happy	no category
waving flag	Happy	Happy
you cant see me	Happy	Happy

Table- 2

We got 25 songs out of 42 test songs correctly matched to the original mood. So our efficiency rate is 59.53% (around 60%).

5.0 Conclusions and Future Work

In this work we have characterized song into different moods using multi layer feed forward neural network with supervised back propagation learning algorithm. We have taken 8 audio features to form one single feature vector and then trained the network with audio features.

Training a neural network is a typical process. A network must be trained with accurate set of feature values and with accurate set of network attribute values. Features extraction is the core part of determination of the mood of a song that is highly dependent on features values. A thorough, deep and accurate study must be made in order to identify best set of features that can be extracted out of an audio song. Any miss of accuracy will definitely produce false results.

Experimental results show the robustness of the system. The system classifies audio into happy, angry and sad mood.

Although we've taken care of accuracy as best we can do, still trained network has produced only 60% efficiency.

The mood classification system was developed as a feasibility study for the development of a system that would classify, successfully, music files according to their mood . This section will discuss future work that needs to be done in order to further study this problem and develop such a system.

Bibliography

- [1] P. Ekman. An argument for basic emotions. *Cognition & Emotion*, 6(3/4):169–200, 1992.
- [2] J. A. Russell. Affective space is bipolar. *Journal of Personality and Social Psychology*,37(3):345–356, 1979.
- [3] J. A. Russell. A circumplex model of affect. *Journal of Personality and Social Psychology*,39(6):1161–1178, 1980.
- [4] R. E. Thayer. *The Biopsychology of Mood and Arousal*. Oxford University Press, Oxford, 1989.
- [5] R. E. Thayer. *The origin of everyday moods: managing energy, tension, and stress*. Oxford University Press, New York, 1996.
- [6] A. Mehrabian. Pleasure-arousal-dominance: A general framework for describing and measuring individual. *Current Psychology*, 14(4):261–292, 1996.
- [7] Y. Feng, Y. Zhuang, and Y. Pan. Music information retrieval by detecting mood via computational media aesthetics. In *Proceedings of the IEEE/WIC International Conference on Web Intelligence*, page 235, Washington, USA, 2003.
- [8] [24] P.N.Juslin. Cue utilization in communication of emotion in music performance: relating performance to perception. *Journal of Experimental Psychology: Human Perception and Performance*, 26(6):1797–1813, 2000.
- [9] S. Dixon. A lightweight multi-agent musical beat tracking system. In *Proceedings of the Pacific Rim International Conference on Artificial Intelligence*, pages 778–788, Melbourne, Australia, 2000.

- [10] K. Hevner. Experimental studies of the elements of expression in music. *The American Journal of Psychology*, 48(2):246–268, 1936.
- [11] C.H. Chen, M.F. Weng, S.K. Jeng, and Y.Y. Chuang. Emotion-Based Music Visualization Using Photos. *LNCS*, 4903:358–368, 2008.
- [12] P. R. Farnsworth. A study of the hevner adjective list. *The Journal of Aesthetics and Art Criticism*, 13(1):97–103, 1954.
- [13] M. G. Rigg. What Features of a Musical Phrase Have Emotional Suggestiveness?, volume 36 of *Bulletin of the Oklahoma Agricultural and Mechanical College*. Oklahoma Agricultural and Mechanical College, Stillwater, Oklahoma, 1939.
- [14] M. G. Rigg. The mood effects of music: A comparison of data from four investigators. *The Journal of Psychology*, 58:427–438, 1964.
- [15] K. B. Watson. The nature and measurement of musical meanings. In *Psychological Monographs*, volume 54, pages 1–43. The American Psychological Association, Evanston, IL, 1942.
- [16] L. Lu, D. Liu, and H.J. Zhang. Automatic mood detection and tracking of music audio signals. *IEEE Trans. Audio, Speech & Language Process*, 14(1), 2006.
- [17] T.L. Wu and S.K. Jeng. Probabilistic estimation of a novel music emotion model. In *14th International Multimedia Modeling Conference*. Springer, 2008.
- [18] S. Kim, S. Kim, S. Kwon, and H. Kim. A music summarization scheme using tempo racking and two stage clustering. *IEEE Workshop on Multimedia Signal Processing*, pages 225–28, 2006.
- [19] L. Lu, D. Liu, and H.J. Zhang. Automatic mood detection and tracking of music audio signals. *IEEE Trans. Audio, Speech & Language Process*, 14(1), 2006.
- [20] C.C. Liu, Y.H. Yang, P.H. Wu, and H.H. Chen. Detecting and classifying emotion in popular music. In *JCIS*, 2006.
- [21] Sanjay Jain and R.S. Jadon, “Audio Based Movies Characterization using Neural Network”, published in *International Journal of Computer Science and Applications (IJCSA ISSN 0974-1003)*, Vol 1 No.2, PP 87-91, Aug, 2008.
- [22] Sanjay Jain and R.S. Jadon, “Features Extraction for Movie Genres Characterization”, in *Proceeding of WCVGIP-06*, 2006.
- [23] T. Li and M. Ogihara. Content-based music similarity search and emotion detection. In *Proceedings of the IEEE International Conference on Acoustics, Speech, and Signal Processing*, volume 5, pages 705–708, 2004.
- [24] G. Tzanetakis and P. Cook. Marsyas: a framework for audio analysis. *Organised Sound*, 4(3):169–175, 1999.
- [25] A. Tellegen, D. Watson, and L. A. Clark. On the dimensional and hierarchical structure of affect. *Psychological Science*, 10(4):297–303, 1999.
- [26] D. Yang and W. Lee. Disambiguating music emotion using software agents. In *Proceedings of the 5th*

International Conference on Music Information Retrieval,
Barcelona, Spain, 2004.

[27] M. Tolos, R. Tato, and T. Kemp. Mood-based navigation through large collections of musical data. In Consumer Communications and Networking Conference, pages 71–75, Las Vegas, USA, 2005.

[28] A. Wiczorkowska, P. Synak, R. Lewis, and Z. Ras. Extracting emotions from music data. In Proceedings of the 15th International Symposium on Methodologies for Intelligent Systems, Saratoga Springs, USA, 2005.

[29] www.mathworks.com/help/pdf_doc/nnet/nnet_ug.pdf.

[30] www.mathworks.com/products/neural-network/